




6100 Series Projecting Fire Dept. Inlet Connections



GUARDIAN
FIRE EQUIPMENT, INC.




6114



6124/6126



6136



Function

- Used as auxiliary connections through which the fire department can pump water to supplement existing water supplies
- Provides 250 GPM flow (minimum), per 2½" inlet

Features/Components

- **Two and three-way** inlet connections feature clappered brass bodies (straight pattern), with female hose thread swivel inlets and female NPT outlets
- **Standard components, all connections:**
Plugs with chains and identification plate
- Cast brass construction*, standard

*Optional brass finishes, add suffix to model no.

-B Polished; -C Rough Chrome Plated; -D Polished Chrome Plated

Two and Three-Way Connections

Model No.	Size	Clappers	A	B	D
6114	4" x 2½" x 2½"	1	5⅞"	8⅞"	10"
6124	4" x 2½" x 2½"	2	7⅞"	10½"	10"
6126	6" x 2½" x 2½"	2	8"	10½"	11¼"
6134	4" x 2½" x 2½" x 2½"	3	10½"	13¾"	10"
6136	6" x 2½" x 2½" x 2½"	3	11¼"	13¾"	11¼"

Identification Plate Lettering:

- AUTO SPKR
- AUTO SPKR & STANDPIPE
- STANDPIPE
- DRY STANDPIPE

Notes

- Always specify hose threads and identification plate lettering
- Contact Guardian for current approvals and special requirements