



Accommodates

- Fire Extinguisher

Standard Construction & Features

- One piece 20 gauge cold-rolled steel door and frame, 18 gauge steel box
- Door is reinforced with rigid tubular metal
- Continuous steel piano hinge and pin
- White baked acrylic enamel finish*
- Door handle hardware

*Suitable as prime or finish coat

Optional Door & Frame Materials

- Add prefix **AL** to cabinet model no. for aluminum (clear anodized finish)
- Add prefix **SS** to cabinet model no. for 304 stainless steel (#4 brushed finish)
- Add suffix **-RED** to steel cabinet model no. for red baked acrylic enamel finish

Refer to page 5 for details



1900 Series

Ordering Procedure

- Select cabinet model number
- Select cabinet door style (refer to page 6)
- Select fire extinguisher (refer to pages 43 to 45)

Standard Construction


Model No.	Mounting Style	Trim A	Inside Box Dimensions			Frame O.D.*		Wall Opening			ADA	Accommodates Guardian Extinguishers
			B	C	D	E	F	Width	Height	Depth		
1910	Trimless	--	12"	27"	8"	--	--	13"	28"	8 1/2"	✓	Any Dry Chemical CO ₂ : 5 & 10 lb. Any Halotron1
1920	Recessed	3/8"	12"	27"	8"	15 1/2"	30 1/2"	13"	28"	8 1/4"	✓	
1930	Semi-Rec.	1 1/4"	12"	27"	8"	15 1/2"	30 1/2"	13"	28"	7 1/4"	✓	
1940	Semi-Rec.	2 1/2"	12"	27"	8"	15 1/2"	30 1/2"	13"	28"	6"	✓	
1945	Semi-Rec.	4 1/2"	12"	27"	8"	15 1/2"	30 1/2"	13"	28"	4"	No	
1950	Surface	9"	15 1/2"	30 1/2"	8 1/4"	15 1/2"	30 1/2"	--	--	--	No	Water, Foam: 2 1/2 gal.

*Deduct 3/4" O.D. for aluminum door and frame


Fire-Rated

Model No.	Mounting Style	Trim A	Inside Box Dimensions			Frame O.D.		Wall Opening			ADA	Accommodates Guardian Extinguishers
			B	C	D	E	F	Width	Height	Depth		
FR1920	Recessed	3/8"	12"	27"	8"	15 1/2"	30 1/2"	14 1/8"	29 1/8"	9 1/8"	✓	Any Dry Chemical CO ₂ : 5 & 10 lb. Any Halotron1 Water, Foam: 2 1/2 gal.
FR1930	Semi-Rec.	1 1/4"	12"	27"	8"	15 1/2"	30 1/2"	14 1/8"	29 1/8"	8 1/8"	✓	
FR1940	Semi-Rec.	2 1/2"	12"	27"	8"	15 1/2"	30 1/2"	14 1/8"	29 1/8"	7"	✓	
FR1945	Semi-Rec.	4 1/2"	12"	27"	8"	15 1/2"	30 1/2"	14 1/8"	29 1/8"	4 7/8"	No	


Note: Fire-Rated cabinets are fabricated in accordance with **WARNOCK HERSEY** certified designs and labelled for 1 and 2-hour combustible and non-combustible walls. Boxes are double-wall construction, lined with fire resistant material.




Trimless



Recessed



Semi-Rec.



Surface