



ABC-Stored Pressure



- Mono ammonium phosphate based dry chemical
- Chemically insulates **Class A** fires/smolders and breaks the chain reaction of **Class B** fires/non-conductor of **electricity (C)**
- UL and Coast Guard* approved

Model No.	Size & Capacity	UL Rating	Range	Discharge Time	Height	Width	Depth
4002	2½ lbs.	1A:10B:C	9-15'	10s.	14⅝"	5¾"	3"
4002T	2½ lbs.	1A:10B:C	9-15'	10s.	14⅝"	5¾"	3"
4005	5 lbs.	2A:10B:C	12-18'	14s.	15¼"	7¼"	4¼"
4005T	5 lbs.	2A:10B:C	12-18'	14s.	15¼"	7¼"	4"
4006	6 lbs.	3A:40B:C	12-18'	14s.	16"	7¾"	5⅝"
4010	10 lbs.	4A:80B:C	15-21'	20s.	20"	7¾"	5⅝"
4020	20 lbs.	10A:120B:C	15-21'	30s.	23¼"	10¼"	7½"



BC-Stored Pressure



- Sodium bicarbonate based dry chemical
- Chemically smothers and breaks the chain reaction of **Class B** fires/non-conductor of **electricity (C)**
- UL and Coast Guard* approved

Model No.	Size & Capacity	UL Rating	Range	Discharge Time	Height	Width	Depth
4102T	2½ lbs.	10B:C	9-15'	10s.	14⅝"	5¾"	3"
4105	5 lbs.	10B:C	12-18'	10s.	15¼"	7¼"	4¼"
4105T	5 lbs.	10B:C	12-18'	10s.	15¼"	5½"	4¼"
4110	10 lbs.	60B:C	15-21'	18s.	20"	7¾"	5¼"
4120	20 lbs.	120B:C	15-21'	28s.	23¼"	10¼"	7½"



Purple K-Stored Pressure



- Potassium bicarbonate based dry chemical
- Chemically smothers and breaks the chain reaction of **Class B** fires/non-conductor of **electricity (C)**
- UL and Coast Guard* approved

Model No.	Size & Capacity	UL Rating	Range	Discharge Time	Height	Width	Depth
4202T	2½ lbs.	10B:C	9-15'	10s.	14⅝"	5¾"	3"
4205T	5 lbs.	30B:C	12-18'	12s.	15¼"	7¼"	4¼"
4210	10 lbs.	80B:C	15-21'	22s.	20"	8¾"	5⅝"
4220	20 lbs.	120B:C	15-21'	28s.	23¼"	10¼"	7¼"



*Refer to page 46 for Coast Guard approved extinguisher/bracket combinations