







Function and Features

- Provides means for quick delivery of fire fighting agent suitable to the hazard
- Design permits single-person transport and operation
- Dry chemical (ABC, BC, and Purple K) available as stored pressure, direct pressure and regulated pressure models
- All extinguishers are UL listed/Coast Guard approved

Agents/Classes

- **ABC** - Mono ammonium phosphate based dry chemical... 
- **BC** - Sodium bicarbonate based dry chemical..... 
- **Purple K** - Potassium bicarbonate based dry chemical.... 
- **CO₂** - Clean, non-contaminating odorless gas..... 



| OP * | Model No. | Agent | Size & Capacity | UL Rating | Nitro. Cyl. | Discharge Range/Time | Hose L. x Dia. | Wheels** | Dimensions |
|---|-----------|-----------------|-----------------|------------|---------------------|----------------------|----------------|---------------------|-----------------|
| S t o r e d | 4705 | ABC | 50 lbs. | 20A:160B:C | --- | 25'-35'/35s | 25' x 1/2" | SP 12 1/2" x 3 1/2" | 46" x 22" x 24" |
| | 4705B | BC | 50 lbs. | 160B:C | --- | 25'-35'/35s | 25' x 1/2" | SP 12 1/2" x 3 1/2" | 46" x 22" x 24" |
| | 4705K | Purple K | 50 lbs. | 160B:C | --- | 25'-35'/35s | 25' x 1/2" | SP 12 1/2" x 3 1/2" | 46" x 22" x 24" |
| | 4715 | ABC | 125 lbs. | 30A:240B:C | --- | 30'-40'/48s. | 50' x 3/4" | SP 16" x 4" | 54" x 28" x 40" |
| | 4715B | BC | 150 lbs. | 240B:C | --- | 30'-40'/48s. | 50' x 3/4" | SP 16" x 4" | 54" x 28" x 40" |
| | 4715K | Purple K | 125 lbs. | 240B:C | --- | 30'-40'/48s. | 50' x 3/4" | SP 16" x 4" | 54" x 28" x 40" |
| - | 4725 | CO ₂ | 50 lbs. | 20B:C | --- | 10'-15'/44±5s. | 15' x 1/4" | FP 16" x 4" | 47" x 23" x 48" |
| | 4730 | CO ₂ | 100 lbs. | 20B:C | --- | 10'-15'/74±8s. | 40' x 1/4" | FP 16" x 4" | 47" x 23" x 48" |
| D i r e c t | 4815 | ABC | 125 lbs. | 30A:240B:C | 23 ft ³ | 30'-40'/52s. | 50' x 3/4" | SP 16" x 4" | 45" x 24" x 36" |
| | 4815B | BC | 150 lbs. | 240B:C | 23 ft ³ | 30'-40'/60s. | 50' x 3/4" | SP 16" x 4" | 45" x 24" x 36" |
| | 4815K | Purple K | 125 lbs. | 320B:C | 23 ft ³ | 30'-40'/53s. | 50' x 3/4" | SP 16" x 4" | 45" x 24" x 36" |
| | 4835 | ABC | 300 lbs. | 40A:240B:C | 55 ft ³ | 30'-40'/60s. | 50' x 1" | ST 36" x 6" | 57" x 34" x 39" |
| | 4835B | BC | 350 lbs. | 320B:C | 55 ft ³ | 30'-40'/70s. | 50' x 1" | ST 36" x 6" | 57" x 34" x 39" |
| | 4835K | Purple K | 300 lbs. | 320B:C | 55 ft ³ | 30'-40'/67s. | 50' x 1" | ST 36" x 6" | 57" x 34" x 39" |
| R e g u l a t e d | 4915 | ABC | 125 lbs. | 30A:240B:C | 110 ft ³ | 30'-40'/48s. | 50' x 3/4" | ST 36" x 2 1/2" | 52" x 26" x 38" |
| | 4915B | BC | 150 lbs. | 240B:C | 110 ft ³ | 30'-40'/53s. | 50' x 3/4" | ST 36" x 2 1/2" | 52" x 26" x 38" |
| | 4915K | Purple K | 125 lbs. | 320B:C | 110 ft ³ | 30'-40'/52s. | 50' x 3/4" | ST 36" x 2 1/2" | 52" x 26" x 38" |
| | 4925 | ABC | 125 lbs. | 30A:240B:C | 110 ft ³ | 30'-40'/48s. | 50' x 3/4" | SP 16" x 4" | 52" x 26" x 38" |
| | 4925B | BC | 150 lbs. | 240B:C | 110 ft ³ | 30'-40'/53s. | 50' x 3/4" | SP 16" x 4" | 52" x 26" x 38" |
| | 4925K | Purple K | 125 lbs. | 320B:C | 110 ft ³ | 30'-40'/52s. | 50' x 3/4" | SP 16" x 4" | 52" x 26" x 38" |

*OP = Operating type (Stored pressure, direct pressure, and regulated pressure)

**Wheels SP = Semi Pneumatic
ST = Steel
FP = Full Pneumatic