

Accommodates

- 2½" Fire Dept. Valve

Standard Construction & Features

- One piece 20 gauge cold-rolled steel door and frame, 18 gauge steel box
- Door is reinforced with rigid tubular metal
- Continuous steel piano hinge and pin
- White baked acrylic enamel finish*
- Door handle hardware


*Suitable as prime or finish coat

Optional Door & Frame Materials


- Add prefix **AL** to cabinet model no. for aluminum (clear anodized finish)
- Add prefix **SS** to cabinet model no. for 304 stainless steel (#4 brushed finish)
- Add suffix **-RED** to steel cabinet model no. for red baked acrylic enamel finish

Refer to page 5 for details


2000 Series




Trimless



Recessed



Semi-Rec.



Surface

Trimless, recessed & semi-rec. cabinets furnished with combination knockouts (1½" & 2½") on both sides of box.

Ordering Procedure

- Select cabinet model number
- Select cabinet door style (refer to page 6)
- Select fire dept. valve (refer to page 50)

Standard Construction

Model No.	Mounting Style	Trim A	Inside Box Dimensions				Frame O.D.*		Knockout Location		Wall Opening			ADA
			B	C	D	E	F	G	H	Width	Height	Depth		
2010	Trimless	--	18"	18"	8"	--	--	4"	9"	19"	19"	8½"	✓	
2020	Recessed	⅜"	18"	18"	8"	21½"	21½"	4"	9"	19"	19"	8¼"	✓	
2030	Semi-Rec.	1¼"	18"	18"	8"	21½"	21½"	4"	9"	19"	19"	7¼"	✓	
2040	Semi-Rec.	2½"	18"	18"	8"	21½"	21½"	4"	9"	19"	19"	6"	✓	
2050	Surface	9"	21½"	21½"	8½"	21½"	21½"	--	--	--	--	--	No	

*Deduct ¼" O.D. for aluminum door and frame

Fire-Rated

Model No.	Mounting Style	Trim A	Inside Box Dimensions				Frame O.D.*		Knockout Location		Wall Opening			ADA
			B	C	D	E	F	G	H	Width	Height	Depth		
FR2020	Recessed	⅜"	18"	18"	8"	21½"	21½"	--	--	20⅞"	20⅞"	9⅞"	✓	
FR2030	Semi-Rec.	1¼"	18"	18"	8"	21½"	21½"	--	--	20⅞"	20⅞"	8⅞"	✓	
FR2040	Semi-Rec.	2½"	18"	18"	8"	21½"	21½"	--	--	20⅞"	20⅞"	7"	✓	

Notes: Fire-Rated cabinets are fabricated in accordance with **WARNOCK HERSEY** certified designs and labelled for 1 and 2-hour combustible and non-combustible walls.

Boxes are double-wall construction, lined with fire resistant material.

Option: 10" deep box dimension, add suffix **-10** to model no. to specify