



Function

- Used as auxiliary connections to supply water for fire department use and for testing of standpipe system
- Provides 250 GPM flow (minimum), per 2½" outlet

Features/Components

- **Two and three-way** outlet connections feature brass bodies (straight or angle pattern), with female NPT inlets and male NPT outlets (female NPT outlets on **Models 6944/6946**)
- Cast brass construction

Two and Three-Way Connections

Model No.	Inlet	Size	A	B
6924	back	4" x 2½" x 2½"	6⅝"	4¾"
6925	angle	4" x 2½" x 2½"	6¾"	5¾"
6926	back	6" x 2½" x 2½"	8¼"	6⅜"
6927	angle	6" x 2½" x 2½"	9"	8½"
6935	angle	4" x 2½" x 2½" x 2½"	13½"	10½"
6936	back	6" x 2½" x 2½" x 2½"	10¼"	10⅝"
6937	angle	6" x 2½" x 2½" x 2½"	10½"	9"
6944	end	4" x 4" x 2½" x 2½" x 2½"	5"	19"
6946	end	6" x 6" x 2½" x 2½" x 2½"	7¼"	19"

Components & Variation

Suffix

- **1** Standard bodies, complete with **Model 5015** angle valves and **Model 5525** caps for each outlet
- **2** Standard bodies, complete with **Model 5110** gate valves and **Model 5525** caps for each outlet
- **3** Standard bodies, complete with **Model 5310** globe valves and **Model 5525** caps for each outlet
- **NST** Bodies with male hose thread outlets *overall dimensions may vary*


To specify components or variation, add suffix to model no.

Notes


- Pipe nipple outlets for **Models 6944/6946** by others
- Contact factory for current UL listing/FM approvals and special requirements




6924/6926




6925/6927



6936



6935/6937



6944/6946

