



# GUARDIAN

FIRE EQUIPMENT, INC.  
MIAMI, FL

Ph. 800.327.6584 • Fax 800.827.3869

## DETAIL AND SUBMITTAL SHEET

### 4000-4200 Series - Portable Fire Extinguishers

Project/Location: \_\_\_\_\_

Date: \_\_\_\_\_

Architect/Engineer: \_\_\_\_\_

Qty: \_\_\_\_\_

Contractor: \_\_\_\_\_

Appropriate Selection

#### ABC-Stored Pressure

Mono ammonium phosphate based dry chemical. Chemically insulates Class A fires/smolders and breaks the chain reaction of Class B fires/non-conductor of electricity (C). UL and Coast Guard approved.

Model No.	Size & Capacity	UL Rating	Range	Discharge Time	Height	Width	Depth
<input type="checkbox"/> 4002	2½ lbs.	1A:10B:C	9-15'	10s.	14 <sup>5</sup> / <sub>8</sub> "	5 <sup>3</sup> / <sub>4</sub> "	3"
<input type="checkbox"/> 4002T	2½ lbs.	1A:10B:C	9-15'	10s.	14 <sup>5</sup> / <sub>8</sub> "	5 <sup>3</sup> / <sub>4</sub> "	3"
<input type="checkbox"/> 4005	5 lbs.	2A:10B:C	12-18'	14s.	15 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>4</sub> "	4 <sup>1</sup> / <sub>4</sub> "
<input type="checkbox"/> 4005T	5 lbs.	2A:10B:C	12-18'	14s.	15 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>4</sub> "	4"
<input type="checkbox"/> 4006	6 lbs.	3A:40B:C	12-18'	14s.	16"	7 <sup>3</sup> / <sub>4</sub> "	5 <sup>1</sup> / <sub>8</sub> "
<input type="checkbox"/> 4010	10 lbs.	4A:80B:C	15-21'	20s.	20"	7 <sup>3</sup> / <sub>4</sub> "	5 <sup>1</sup> / <sub>8</sub> "
<input type="checkbox"/> 4020	20 lbs.	10A:120B:C	15-21'	30s.	23 <sup>1</sup> / <sub>4</sub> "	10 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>2</sub> "



#### BC-Stored Pressure

Sodium bicarbonate based dry chemical. Chemically smothers and breaks the chain reaction of Class B fires/non-conductor of electricity (C). UL and Coast Guard approved.

Model No.	Size & Capacity	UL Rating	Range	Discharge Time	Height	Width	Depth
<input type="checkbox"/> 4102T	2½ lbs.	10 B:C	9-15'	10s.	14 <sup>5</sup> / <sub>8</sub> "	5 <sup>3</sup> / <sub>4</sub> "	3"
<input type="checkbox"/> 4105	5 lbs.	10 B:C	12-18'	14s.	15 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>4</sub> "	4 <sup>1</sup> / <sub>4</sub> "
<input type="checkbox"/> 4105T	5 lbs.	10 B:C	12-18'	10s.	15 <sup>1</sup> / <sub>4</sub> "	5 <sup>1</sup> / <sub>2</sub> "	4 <sup>1</sup> / <sub>4</sub> "
<input type="checkbox"/> 4110	10 lbs.	60 B:C	15-21'	18s.	20"	7 <sup>3</sup> / <sub>4</sub> "	5 <sup>1</sup> / <sub>4</sub> "
<input type="checkbox"/> 4120	20 lbs.	120 B:C	15-21'	28s.	23 <sup>1</sup> / <sub>4</sub> "	10 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>2</sub> "



#### Purple K-Stored Pressure

Potassium bicarbonate based dry chemical. Chemically smothers and breaks the chain reaction of Class B fires/non conductor of electricity (C). UL and Coast Guard approved.

Model No.	Size & Capacity	UL Rating	Range	Discharge Time	Height	Width	Depth
<input type="checkbox"/> 4202T	2½ lbs.	10 B:C	9-15'	10s.	14 <sup>5</sup> / <sub>8</sub> "	5 <sup>3</sup> / <sub>4</sub> "	3"
<input type="checkbox"/> 4205	5 lbs.	30 B:C	12-18'	12s.	15 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>4</sub> "	4 <sup>1</sup> / <sub>4</sub> "
<input type="checkbox"/> 4210	10 lbs.	80 B:C	15-21'	22s.	20"	8 <sup>3</sup> / <sub>4</sub> "	5 <sup>1</sup> / <sub>8</sub> "
<input type="checkbox"/> 4220	20 lbs.	120 B:C	15-21'	28s.	23 <sup>1</sup> / <sub>4</sub> "	10 <sup>1</sup> / <sub>4</sub> "	7 <sup>1</sup> / <sub>4</sub> "



Model numbers ending with "T" indicate Vehicle/Marine bracket. All other extinguishers supplied with standard wall bracket.