



GUARDIAN

FIRE EQUIPMENT, INC.
MIAMI, FL

Ph. 800.327.6584 • Fax 800.827.3869

DETAIL AND SUBMITTAL SHEET

4700-4900 Series - Wheeled Fire Extinguishers

Project/Location: _____

Date: _____

Architect/Engineer: _____

Qty: _____

Contractor: _____

Appropriate Selection

Wheeled Fire Extinguishers


Provides means for quick delivery of fire fighting agent suitable to the hazard. Design permits single-person transport and operation. Dry chemical (ABC, BC and Purple K) available as stored pressure, direct pressure and regulated pressure models. All extinguishers are UL listed/Coast Guard approved.



4715



4725



4815

OP*	Model No.	Agent	Size & Capacity	UL Rating	Nitro. Cyl.	Discharge Range/Time	Hose L. x Dia.	Wheels**	Dimensions
S t o r e d	<input type="checkbox"/> 4705	ABC	50 lbs.	20A:160B:C	---	25'-35'/35s.	25' x 1/2"	SP 12 1/2" x 3 1/2"	46" x 22" x 24"
	<input type="checkbox"/> 4705B	BC	50 lbs.	160B:C	---	25'-35'/35s.	25' x 1/2"	SP 12 1/2" x 3 1/2"	46" x 22" x 24"
	<input type="checkbox"/> 4705K	Purple K	50 lbs.	160B:C	---	25'-35'/35s.	25' x 1/2"	SP 12 1/2" x 3 1/2"	46" x 22" x 24"
	<input type="checkbox"/> 4715	ABC	125 lbs.	30A:240B:C	---	30'-40'/48s.	50' x 3/4"	SP 16" x 4"	54" x 28" x 40"
	<input type="checkbox"/> 4715B	BC	150 lbs.	240B:C	---	30'-40'/48s.	50' x 3/4"	SP 16" x 4"	54" x 28" x 40"
	<input type="checkbox"/> 4715K	Purple K	125 lbs.	240B:C	---	30'-40'/48s.	50' x 3/4"	SP 16" x 4"	54" x 28" x 40"
-	<input type="checkbox"/> 4725	CO ₂	50 lbs.	20B:C	---	10'-15'/44 ±5s.	15' x 1/4"	FP 16" x 4"	47" x 23" x 48"
	<input type="checkbox"/> 4730	CO ₂	100 lbs.	20B:C	---	10'-15'/74 ±8s.	40' x 1/4"	FP 16" x 4"	47" x 23" x 48"
D i r e c t	<input type="checkbox"/> 4815	ABC	125 lbs.	30A:240B:C	23 ft ³	30'-40'/52s.	50' x 3/4"	SP 16" x 4"	45" x 24" x 36"
	<input type="checkbox"/> 4815B	BC	150 lbs.	240B:C	23 ft ³	30'-40'/60s.	50' x 3/4"	SP 16" x 4"	45" x 24" x 36"
	<input type="checkbox"/> 4815K	Purple K	125 lbs.	320B:C	23 ft ³	30'-40'/53s.	50' x 3/4"	SP 16" x 4"	45" x 24" x 36"
	<input type="checkbox"/> 4835	ABC	300 lbs.	40A:240B:C	55 ft ³	30'-40'/60s.	50' x 1"	ST 36" x 6"	57" x 34" x 39"
	<input type="checkbox"/> 4835B	BC	350 lbs.	320B:C	55 ft ³	30'-40'/70s.	50' x 1"	ST 36" x 6"	57" x 34" x 39"
	<input type="checkbox"/> 4835K	Purple K	300 lbs.	320B:C	55 ft ³	30'-40'/67s.	50' x 1"	ST 36" x 6"	57" x 34" x 39"
R e g u l a t e d	<input type="checkbox"/> 4915	ABC	125 lbs.	30A:240B:C	110 ft ³	30'-40'/48s.	50' x 3/4"	ST 36" x 2 1/2"	52" x 26" x 38"
	<input type="checkbox"/> 4915B	BC	150 lbs.	240B:C	110 ft ³	30'-40'/53s.	50' x 3/4"	ST 36" x 2 1/2"	52" x 26" x 38"
	<input type="checkbox"/> 4915K	Purple K	125 lbs.	320B:C	110 ft ³	30'-40'/52s.	50' x 3/4"	ST 36" x 2 1/2"	52" x 26" x 38"
	<input type="checkbox"/> 4925	ABC	125 lbs.	30A:240B:C	110 ft ³	30'-40'/48s.	50' x 3/4"	SP 16" x 4"	52" x 26" x 38"
	<input type="checkbox"/> 4925B	BC	150 lbs.	240B:C	110 ft ³	30'-40'/53s.	50' x 3/4"	SP 16" x 4"	52" x 26" x 38"
	<input type="checkbox"/> 4925K	Purple K	125 lbs.	320B:C	110 ft ³	30'-40'/52s.	50' x 3/4"	SP 16" x 4"	52" x 26" x 38"

* OP = Operating type (Stored pressure, direct pressure and regulated pressure)

** Wheels SP = Semi Pneumatic
ST = Steel
FP = Full Pneumatic