



GUARDIAN

FIRE EQUIPMENT, INC.
MIAMI, FL

Ph. 800.327.6584 • Fax 800.827.3869

DETAIL AND SUBMITTAL SHEET

3400 Series - Fire Hose

Project/Location: _____

Date: _____

Architect/Engineer: _____

Qty: _____

Contractor: _____


Appropriate Selection

Rack and Reel Hose - Lightweight, thermo-plastic lined

Use: Interior fire protection

| Model No. | Size | Bowl (coupling no.) | Acceptance/Service Test |
|--|------|--|-------------------------|
| <input type="checkbox"/> 3402 | 1½" | 1 ¹³ / ₁₆ " (3480) | 500/250 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |

Select: Coupled - Brass Coupled - Aluminum Uncoupled
Threads: NST Other _____
Options: -UL UL label



3402

Industrial Single Jacket Hose - Single jacket, EPDM rubber lined

Use: Interior/exterior fire protection and washdown

| Model No. | Size | Bowl (coupling no.) | Acceptance/Service Test |
|--|------|--|-------------------------|
| <input type="checkbox"/> 3422 | 1½" | 1 ¹³ / ₁₆ " (3482) | 400/200 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |
| <input type="checkbox"/> 3424 | 2½" | 2 ¹³ / ₁₆ " (3486) | 500/250 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |

Select: Coupled - Brass Coupled - Aluminum Uncoupled
Threads: NST Other _____
Options: -UL UL label -HY Hypalon impreg jacket



3422-3424

Industrial Double Jacket Hose - Double jacket, EPDM rubber lined

Use: Interior/exterior fire protection and washdown

| Model No. | Size | Bowl (coupling no.) | Acceptance/Service Test |
|--|------|--|-------------------------|
| <input type="checkbox"/> 3452 | 1½" | 1 ¹⁵ / ₁₆ " (3483) | 800/400 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |
| <input type="checkbox"/> 3454 | 2½" | 3" (3487) | 800/400 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |

Select: Coupled - Brass Coupled - Aluminum Uncoupled
Threads: NST Other _____
Options: -UL UL label -HY Hypalon impreg jacket




3452-3454

Industrial Nitrile/Rubber Covered Hose - Extruded thru-the-weave construction

Use: Interior/exterior fire protection and washdown

| Model No. | Size | Bowl (coupling no.) | Acceptance/Service Test |
|--|------|--|-------------------------|
| <input type="checkbox"/> 3472 | 1½" | 1 ¹³ / ₁₆ " (3482) | 500/250 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |
| <input type="checkbox"/> 3474 | 2½" | 2 ¹³ / ₁₆ " (3486) | 500/250 PSI |
| Hose Length: <input type="checkbox"/> 50' <input type="checkbox"/> 75' <input type="checkbox"/> 100' | | | |

Select: Coupled - Brass Coupled - Aluminum Uncoupled
Threads: NST Other _____



3472-3474