



# GUARDIAN

FIRE EQUIPMENT, INC.  
MIAMI, FL

Ph. 800.327.6584 • Fax 800.827.3869

## DETAIL AND SUBMITTAL SHEET

### 5000 Series - Hose Valves

Project/Location: \_\_\_\_\_

Date: \_\_\_\_\_

Architect/Engineer: \_\_\_\_\_

Qty: \_\_\_\_\_

Contractor: \_\_\_\_\_

**Appropriate Selection**

**Female x Male Angle Valves** - Used as fire hose outlet connections. Female NPT (or Groove) inlet x Male hose thread outlet, 300 PSI, cast brass

Model No.	Size	A	B (Open)	C	D	Swing Radius
<input type="checkbox"/> 5010	1½" x 1½"	4"	7¾"	2¼"	2"	2½"
<input type="checkbox"/> 5015	2½" x 2½"	5¼"	11"	3¼"	2¾"	3½"
<input type="checkbox"/> 5015G	2½" x 2½"	5½"	11¾"	3⅝"	3⅝"	5⅝"

Optional Finish:  -B Polished Brass  -C Rough Chrome Plated  -D Polished Chrome Plated

Threads:  NST  Other \_\_\_\_\_

**Female x Female Angle Valves** - Used with hose rack assemblies. Female NPT inlet and outlet, 300 PSI, cast brass

Model No.	Size	A	B (Open)	C	D	Swing Radius
<input type="checkbox"/> 5020	1½" x 1½"	4"	7¾"	2¼"	2"	2½"
<input type="checkbox"/> 5025	2½" x 2½"	5¼"	11"	3¼"	2¾"	3½"

Optional Finish:  -B Polished Brass  -C Rough Chrome Plated  -D Polished Chrome Plated

**Female x Male Pressure Restricting Angle Valves** - Used as fire hose outlet connections. Field-adjustable restricting mechanism reduces water pressure under flowing conditions (175 PSI max. inlet). When full flow is required, restriction can be over-ridden by trained personnel. Female NPT x Male hose thread outlet, 175 PSI, cast brass.

Model No.	Size	A	B (Open)	C	D	Swing Radius
<input type="checkbox"/> 5030	1½" x 1½"	4"	8"	2¼"	2"	2½"
<input type="checkbox"/> 5035	2½" x 2½"	5¼"	11½"	3¼"	2¾"	3½"

Optional Finish:  -B Polished Brass  -C Rough Chrome Plated  -D Polished Chrome Plated

Threads:  NST  Other \_\_\_\_\_

**Female x Female Pressure Restricting Valves** - Used with hose rack assemblies. Field-adjustable restricting mechanism reduces water pressure under flowing conditions (175 PSI max. inlet). When full flow is required, restriction can be over-ridden by trained personnel. Female NPT inlet and outlet, 175 PSI, cast brass.

Model No.	Size	A	B (Open)	C	D	Swing Radius
<input type="checkbox"/> 5040	1½" x 1½"	4"	8"	2½"	2"	2½"
<input type="checkbox"/> 5045	2½" x 2½"	5½"	11½"	3½"	2½"	3½"

Optional Finish:  -B Polished Brass  -C Rough Chrome Plated  -D Polished Chrome Plated

**Caps with Chains - Caps with Chains** - Used to protect hose thread outlets on valves and hydrants.


Cast brass caps (pin lugs)\* or red plastic caps (rocker lugs).

Model No.	Size	Type
<input type="checkbox"/> 5515	1½"	Brass
<input type="checkbox"/> 5515P	1½"	Plastic
<input type="checkbox"/> 5525	2½"	Brass
<input type="checkbox"/> 5525P	2½"	Plastic

Threads:

NST

Other \_\_\_\_\_



Optional Finish:  -B Polished Brass  -C Rough Chrome Plated  
 -D Polished Chrome Plated

\*Optional:  -RL Rocker lugs

**Reducer** - Used to change outlet size. Rigid pin lug\*, female x male threads.

Model No.	Size
<input type="checkbox"/> 3315	2½" x 1½"

Optional Finish:

-B Polished Brass

-C Rough Chrome Plated

-D Polished Chrome Plated

\*Optional:  -RL Rocker lugs

Threads:

NST

Other \_\_\_\_\_

