



GUARDIAN

FIRE EQUIPMENT, INC.
MIAMI, FL

Ph. 800.327.6584 • Fax 800.827.3869

DETAIL AND SUBMITTAL SHEET

9300 Series - Sprinkler System Monitoring Devices

Project/Location: _____

Date: _____

Architect/Engineer: _____

Qty: _____

Contractor: _____

Appropriate Selection

Waterflow Detectors - Used to monitor water flow in sprinkler lines. Durable metal enclosure with rugged switch assembly, tamper-resistant. Computer-designed vane-type paddle. Two S.P.D.T. synchronized switches. Sealed retard.

| Model No. | Description | Pipe Size | Model No. | Description | Pipe Size |
|-------------------------------|--------------------|-----------|-------------------------------|--------------------|-----------|
| <input type="checkbox"/> 9310 | Tees* | -- | <input type="checkbox"/> 9335 | Sch. 10 through 40 | 3 1/2" |
| <input type="checkbox"/> 9315 | Non-Retard, Tees* | -- | <input type="checkbox"/> 9340 | Sch. 10 through 40 | 4" |
| <input type="checkbox"/> 9320 | Sch. 10 through 40 | 2" | <input type="checkbox"/> 9350 | Sch. 10 through 40 | 5" |
| <input type="checkbox"/> 9325 | Sch. 10 through 40 | 2 1/2" | <input type="checkbox"/> 9360 | Sch. 10 through 40 | 6" |
| <input type="checkbox"/> 9330 | Sch. 10 through 40 | 3" | <input type="checkbox"/> 9380 | Sch. 10 through 40 | 8" |

*Fits Sizes: 1", 1 1/4", 1 1/2" Ferrous and brass threaded tees; 1" CPVC tees;
1", 1 1/4", 1 1/2", 2" Copper sweat tees; 1 1/2" Polybutylene tees



Supervisory Switches - Used to detect tampering or setting changes on control valves, by monitoring open/closed positions. Durable metal enclosure with single-side entry for conduit. Adjustable actuator length. Two S.P.D.T. synchronized switches.

| Model No. | Description |
|-------------------------------|--|
| <input type="checkbox"/> 9390 | For O.S. & Y and pressure regulating valves with pre-installed bracket |
| <input type="checkbox"/> 9391 | For post indicator, butterfly and pressure regulating valves |
| <input type="checkbox"/> 9392 | Plug type, for N.R.S. gate valves, globe, ball and angle valves |



Pressure Switches - Used to supervise air pressure in pipes and tanks, as well as detect activation of automatic water control valves. Alarm and supervisory models. Durable metal enclosure, tamper-resistant assembly.

| Model No. | Description | S.P.D.T. Switches | PSI (Adjustable) |
|-------------------------------|--------------------------------|-------------------|------------------|
| <input type="checkbox"/> 9395 | Alarm pressure switch | 1 | 4-20 |
| <input type="checkbox"/> 9396 | Alarm pressure switch | 2 | 4-20 |
| <input type="checkbox"/> 9397 | Supervisory, low pressure | 1 | 10-100 |
| <input type="checkbox"/> 9398 | Supervisory, high/low pressure | 1 | 10-100 |

